



NAME

COMPANY

PHONE NUMBER

E-MAIL

COUNTRY / STATE

CITY

WinSize Product Application Sheet

Deflagration Flame Arresters—Model 94406/94407

What is the flange size? Materials of Construction (Body & Flame Bank)

1 - What is the normal operating flow?

2 - What is the maximum flow rate?

3- What is the operating pressure?

4 - What is the maximum allowable pressure drop?

5 - What is the operating temperature?

6 - What is the gas/vapor composition?
(Assume NEC Group D Vapors.)

7 - What is the distance from the flame/ignition source?

8 - What is the pressure from the ignition source?

9 - What is the mounting configuration?

10 - What is the Auxillary Connection?
(3/4" NPT Connections.)

11 - If horizontal configuration, straight pipe; specify drain plugs.

12 - If horizontal configuration, straight pipe; list # of pipe bends.

Simply click the "Submit by Email" button at the bottom of this page to send to L&J Technologies. If you have trouble with your e-mail provider, save this form as a PDF onto your desktop and then attach the PDF in your e-mail to sales@ljtechnologies.com. To fax L&J Technologies, send a completed copy to (708) 236-6006. An L&J Technologies Salesperson will contact you promptly to discuss which products best fit your needs. If you have any questions in the meantime, feel free to contact us directly. We look forward to working with you!
By submitting, you agree to the terms of L&J Technologies Privacy Policy and Terms of Use. Visit www.ljtechnologies.com for more information.